

Unit for filtering the recovered Halon / Clean Agent

HFM/5 model

Specifically designed for filtering the recovered and pressurized Halon / Clean Agent



Advantages

The filtration module allows to re-use the recovered and depressurized Halon / Clean Agent eliminating moisture and main contaminant.

It is mandatory to use this device when achieving the following phases:

1. Just after Nitrogen separation phase (with SHN5 unit), in order to get a product complying with the specific properties required for re-using it.
2. Before the separation phase (SHN5 unit), when the product to be treated contains a lot of moisture.

COMPONENTS AND DEVICES

- Stainless steel trolley
- Electrical drive pumping group for liquid Halon / Clean Agent
- Liquid indicator
- Filtering and drying group of great capacity
- Kit of connection hoses with on-off valves and safety cable

HFM/5 model



TECHNICAL SPECIFICATIONS

Filtration of great quantities of Halon / Clean Agent	
Liquid pump capacity	about 7 kg/min
Power supply	220 Volt 50 Hz
Max working pressure	31 bar



> PER MAGGIORI INFORMAZIONI:
> FOR FURTHER INFORMATION CONTACT:
> POUR INFORMATIONS CONTACTER:

DAMOTEK S.r.l.
Via Avv. Giovanni Agnelli, 10 12033 MORETTA (CN) ITALY
Tel: +39 0172 911235
Fax: +39 0172 911322

www.damotek.com
info@damotek.com

