

Powder extinguisher hydraulic testing unit

HT35 model

Easy, safe and fast testing system for fire extinguishers



ADVANTAGES

Low power consumption and easy transport make this unit suitable for testing operations at different sites, inside the workshop or onsite the customer plant. A series of accessories specially designed for testing wheeled extinguishers and fire hoses add versatility to a well-equipped unit.

APPLICATION

The HT35 unit is designed to perform the hydraulic testing of powder extinguishers at a pressure up to 3,5 MPa. With the appropriate accessories, this unit can also test wheeled powder extinguishers and fire hoses.

COMPONENTS AND DEVICES

- > Electric pump for filling/hydraulic testing
- > Rotating vice for fastening and tilting the extinguisher
- > Water recovery tank, capacity 100 l.
- > Inlet/outlet ball valves
- > Water flow indicator
- > Water filter
- > Pressure gauge
- > Fast coupling type air inlet
- > Painted steel framework

STANDARD EQUIPMENT

- > Extinguisher filling/testing/draining hoses
- > Connection for extinguisher testing with M30 x 1,5mm coupling
- > User manual

AVAILABLE MODELS

- > HT35 single phase
- > HT35 three-phase

Extinguisher drying unit



ACCESSORIES ON DEMAND

DESCRIPTION	MODEL
TESTING / DRAINING KIT FOR WHEELED EXTINGUISHERS	HT35WE
FIRE HOSE TESTING AND REWINDING KIT ON TROLLEY	HTM45/70
FILLING/TESTING/DRAINING CONNECTORS FOR SPECIAL USES	

TECHNICAL FEATURES

MODEL	HT35 SINGLE PHASE	HT35 THREE-PHASE
CATALOGUE CODE	MZCZ020	MZCZ021
EXTINGUISHER PLACES	1	1
N° OF EXTINGUISHERS PER HOUR (6 kg CAPACITY)	12	12
MAX WORKING PRESSURE (bar)	50	50
VOLTAGE/FREQUENCY (VAC/Hz)	220/50	400/50
POWER (kW)	1,1	1,1
DIMENSIONS (LxIxh) (mm)	1150x750x700	1150x750x700
WEIGHT (Kg)	70	70

> PER MAGGIORI INFORMAZIONI:
FOR FURTHER INFORMATION CONTACT:
POUR INFORMATIONS CONTACTER:

DAMOTEK S.r.l.
Via Avv. Giovanni Agnelli, 10 12033 MORETTA (CN) ITALY
Tel: +39 0172 911235
Fax: +39 0172 911322

www.damotek.com
info@damotek.com

