

Transportable unit

SKID AC/FG8 model

For fire extinguisher maintenance and refilling



APPLICATIONS

SKID AC/FG8 is a transportable unit including all the key instruments and accessories for powder and CO₂ fire extinguisher maintenance and refilling operations on a single platform.

ADVANTAGES

SKID AC/FG8 unit has been designed to be moved by forklift and easily fastened to the van platform.

Loading and unloading operations are always fast and simple. In this way, the van can be used either for extinguisher maintenance, than for other tasks.

Its compact dimensions and reduced sizing avoid using the complete load space of the van itself.

COMPONENTS AND DEVICES

- > Extinguishing powder transfer unit mounted on sliding support, TOTEM M or TOTEM TS models
- > Liquid CO₂ (from cylinder) transfer unit, model 99D1
- > Air compressor
- > Electronic scale, model ETW100, with removable hand-operated vice, model VIF/BIL
- > Pneumatic vice with a two-hand operated control, model AIR5B
- > Bench vice
- > Drawers cabinet with safety-locking device
- > Cylinder rack (3 places) with safety bars (cylinders not included)
- > Main integrated electric control panel

Transportable unit for fire extinguisher maintenance and refilling



STANDARD EQUIPMENT

- > Standard equipment for powder transfer units, TOTEM series
- > Standard equipment for liquid CO₂ units, 99D1 model
- > Pressure reducer for Nitrogen cylinder
- > Kit for the pressurization of permanent pressure powder-extinguishers
- > Belts for cylinders and recovery drum fastening
- > Main supply cable with roller, length 20 m
- > Users' manual



STANDARD PRODUCTION MODELS

- > SKID AC/FG8 M
- > SKID AC/FG8 TS

OPTIONAL

- > Accessories for standard powder transfer unit (see TOTEM TS or TOTEM M brochures)
- > Accessories for standard CO₂ transfer unit (see 99D1 brochure)

TECHNICAL SPECIFICATIONS

MODEL	SKID AC/FG8 M SINGLE PHASE	SKID AC/FG8 TS SINGLE PHASE
CODE	MXKZ002	MXKZ006
POWDER FLOW RATE (kg/min)	8 ÷ 10 (*)	12 ÷ 15 (*)
CO ₂ FLOW RATE(Kg/h)	420	420
COMPRESSOR		
AIR PRESSURE (bar)	8	8
SCALE LOADING CAPACITY (Kg)	100	100
SCALE DIVISION (g)	10	10
VOLTAGE / FREQUENCY (VAC/Hz)	230/50	230/50
MAX WORKING POWER (kW)	2,5	2,5
DIMENSIONS (LxIxh) (mm)	1250x1200x1200	1250x1200x1400
WEIGHT(Kg)	350	350

(*) depending on the transferred product use and density
Models for different voltages and frequencies are available on request.

PER MAGGIORI INFORMAZIONI:
> FOR FURTHER INFORMATION CONTACT:
POUR INFORMATIONS CONTACTER:

DAMOTEK S.r.l.
Via Avv. Giovanni Agnelli, 10 12033 MORETTA (CN) ITALY
Tel: +39 0172 911235
Fax: +39 0172 911322

www.damotek.com
info@damotek.com

