

Extinguisher drying unit

DRY series

To quickly remove the moisture generated by the hydraulic testing inside extinguishers and portable cylinders



DRY-6

ADVANTAGES

Reduced dimensions and low power consumption make the DRY2 model easy to use in the workshop or on-board a mobile workshop. The unit is also suitable for the cylinders used by scuba diving and the ones for Oxygen use.

The DRY6 unit ensures high productivity by drying several extinguishers at the same time.

As an option, it is possible to have an air temperature control in order to dry also the aluminium or the composite cylinders that do not accept high temperatures.

COMPONENTS AND DEVICES

- > Lateral blower
- > Fast warming resistance
- > Insulated main manifold
- > Timer for work time setting
- > Main switchboard with 24V. controls

AVAILABLE MODELS

- > DRY2 single-phase
- > DRY6 three-phase

Extinguisher drying unit



ACCESSORIES ON DEMAND

DESCRIPTION	MODEL	CODE
ACCESSORY FOR WHEELED EXTINGUISHERS	DRY2WE	AZEE002
ACCESSORY FOR WHEELED EXTINGUISHERS	DRY6WE	AZEE006

TECHNICAL FEATURES

MODEL	DRY2	DRY6/4	DRY6/10
CATALOGUE CODE	MZEE002	MZEE001	MZEE003
EXTINGUISHER PLACES	2	6	6
N° OF EXTINGUISHERS PER HOUR (6 kg CAPACITY)	12	36	48
WHEELED EXTINGUISHER PLACES WITH WE ACCESSORY	1	2	3
N° OF EXTINGUISHERS PER HOUR WITH WE ACCESSORY	2	4	8
VOLTAGE/FREQUENCY (VAC/Hz)	220/50	400/50	400/50
BLOWING POWER (kW)	0,37	1,1	1,5
RESISTANCE POWER (kW)	0,77	4	10
DIMENSIONS (LxIxh) (mm)	870x370x685	2000x500x700	2000x500x700
WEIGHT (Kg)	30	70	75

> PER MAGGIORI INFORMAZIONI:
FOR FURTHER INFORMATION CONTACT:
POUR INFORMATIONS CONTACTER:

DAMOTEK S.r.l.

Via Avv. Giovanni Agnelli, 10 12033 MORETTA (CN) ITALY

Tel: +39 0172 911235

Fax: +39 0172 911322

www.damotek.com

info@damotek.com



ISO 9001